



## Tech Lift M4

### 1.5m Steplift

- Indoor or Outdoor
- Quick Delivery
- Competitively Priced
- One day installation
- 3 Year Warranty\*
- Ultra Slim Design
- Easy to use
- No Specialist Builders Work Required

**LEVEL**

## Features

# Standard Features

Tech Lift M4 is based on 4 telescopic lifting columns which gives the lift a clean and stylish appearance, the operation is almost maintenance-free and has a very quiet drive.

The lift can be used both indoors and outdoors and fits equally well in private and public environments.



01

Suitable for outdoor installations at no extra cost (IP65 rated)

02

Upper and lower gates included - with or without mid-rail

03

Ultra-slim due to telescopic lifting legs

04

Framework in Black (RAL 9005) or Silver (Interpon 700 AS)

05

Plexi-glass vision panels - Smoked or Clear

06

Aluminium platform flooring with Anti-slip strips

07

Wireless wall mounted call station (2 buttons) - 'call & Send'

08

Floor mounted fixed ramp (no need for a pit)

## Features

# Delivery & Installation

✓

Extremely quick delivery, usually from stock

✓

One day installation (to prepared area)

✓

No specialist builders' work required

✓

Can be relocated



# Optional Features

## Emergency Communication

- GSM Autodialler (sim card by client) – required for public access applications (EN81:40 – 1st April 2023 onwards)

## Landing Buttons & Hand-held Controls

- Wireless wall mounted call station:
  - 'Call' (1 button)
  - 'Call & Send' + key locking (2 buttons)
- Hand held key fob transmitter

## Platform Entry

- Tilting ramp / Wheelstop
- Folding ramp (folds when lift leaves landing)
- Pit mount (40m deep)

## Gates

- Automatic openers on one or both gates

## Lift Colour

- Seamlessly blend in with the built environment, match your corporate colours or make a bold design statement, the choice is yours when choosing an optional (RAL) colour.



## Specification

# Tech Lift M4: Technical Specification

<b>Environment</b>	Indoors & Outdoors
<b>Maximum Lifting Height</b>	1.5m / 2 stops (1.46m if pit mounted)
<b>Minimum Platform Size</b>	800mm (w) x 1400mm (L) (wheelchair user)
<b>Standard Platform Size</b>	900mm (w) x 1400mm (L) (Wheelchair User)
<b>Maximum Platform Size</b>	1100mm (w) x 1400mm (L) (wheelchair user + attendant)
<b>Lifting Capacity (max)</b>	400kg
<b>Pit Depth</b>	40mm (if preferred) or simply floor mount with a choice of entry ramp
<b>Travel Speed</b>	40mm/sec max
<b>Entrance Configuration(s)</b>	Through Access
<b>Door Type(s)</b>	Single Swing – Manual or Automatic (optional)
<b>Flooring Type(s)</b>	Aluminium with anti-slip strips
<b>Lift Colours / Finishes</b>	Black RAL9005 or Silver (Interpon 700 AS)
<b>Landing Push Buttons</b>	Wireless
<b>Fixing Method(s)</b>	Floor Mounted and at Threshold (no specialist builders work required)
<b>Power Supply Requirement</b>	220v Single Phase, 6 amp
<b>Conformity</b>	EN-81-41:2010 S: Machine Directive 2006/42/EC
<b>Warranty</b>	3 Years* parts and labour (including two service visits in the first year).



## Contact

**Level Access Lifts Ltd**

t: 023 8081 4924

e: [sales@levellifts.co.uk](mailto:sales@levellifts.co.uk)

w: [levellifts.co.uk](http://levellifts.co.uk)

\*Subject to the uptake of a maintenance contract for years two and three.  
The warranty period shall revert to 12 months if no maintenance agreement in place.

